




DEPARTMENT OF
ENVIRONMENT AND
NATURAL RESOURCES

DENR ADMINISTRATIVE ORDER
NO. 04
SERIES OF 1992

JAN 27 1993


SUBJECT: ADOPTION OF THE "STANDARDIZED ENR
STATISTICAL TERMS AND DEFINITIONS"

1. In the interest of the service and in order to standardize the terms and definitions used by the DENR in all its reports, publications and other issuances, the terms and definitions compiled by the National Mapping and Resource Information Authority (NAMRIA) in coordination with the offices within DENR Proper and Staff Bureaus, the output of the project entitled "Standardization of ENR Terms and Definitions" is hereby adopted as the official DENR glossary of technical terms and definitions on environment and natural resources.
2. NAMRIA shall be the responsible agency for the reproduction and packaging of said document, copies of which shall be distributed to every CENRO, PENRO, Regional Office, Staff Bureaus, Attached Agencies and Offices in the DENR Proper.
3. An annual periodic review of said terms and definitions shall be undertaken by the NAMRIA in coordination with the DENR Technical Statistical Secretariat and the Philippine Statistical Development Program (PSDP) -Task Force on Environment and Natural Resources.
4. This order takes effect immediately and shall remain in force unless amended/revoked in writing.


ANGEL C. ALCALA
Secretary

Recommending approval:


JOSE G. SOLIS
Administrator, NAMRIA


RICARDO M. UMALI
Sr. Undersecretary for Planning,
Policy and Natural
Resources Management

CLASSIFICATION OF STANDING TREES LEFT AFTER LOGGING BASED FROM THE EXTENT OF DAMAGE/INJURY

TREE SECTION	HEALTHY RESIDUAL	DOUBTFUL/SUB-STANDARD	DAMAGED STANDING TREE
Root System	Not more than 1/6 is removed/damaged	Over 1/6 but not more than 1/4 is removed/damaged	More than 1/4 is removed/damaged
Buttress	Not more than 1/3 of the total number of buttresses are battered/damaged	Over 1/3 but not more than 1/2 of the total number of buttresses are battered/damaged.	More than 1/2 of the total number of buttresses are battered/damaged.
Bole or Trunk	Cylindrical, straight and sound for maximum injury reaching the wood is not more than 5 cm wide and 50 cm long along a straight line parallel to the longitudinal axis and not more than 1/2 of the circumference is girdled or indented by wire rope.	Injury reaching the wood is over 5 cm wide to 1/3 of the circumference and not more than 2 meters long along a straight line parallel to the longitudinal axis and more than 1/2 but not more than 2/3 of the circumference is girdled or indented by wire rope.	Injury reaching the wood is more than 1/3 of the circumference and more than 2 meters long along a straight line parallel to the longitudinal axis and more than 2/3 of the circumference is girdled or indented by wire rope.
Crown	Not more than 1/6 is severed or badly damaged.	More than 1/6 but not more than 1/2 is severed or badly damaged.	More than 1/2 is severed or badly damaged.

Note:

Adapted from the Selective Logging Handbook prepared by Forester and Regional Director (Ret.) Isidoro Siagno